

UTV

250-2



Specification	UTV
Engine model	JN172MM/JN1P65YML-6
Battery	12V 9AH
Type	Single Cylinder, Four-Stroke, Horizontal, Forced Air Cooling (oil cooler can be added)
Bore* stroke	65*60
Compression ratio	9.5:1
Working volume of cylinder	199.1mL
Max. engine power (E-mark)	9.3kW/7000r/min
Maximum Speed	37MPH (60KM)
Max. engine torque	Air Cooling
Fuel Grade	92
Lubrication Method	Pressure Splash Type
Starting Model	Electric Starting
Ignition Mode	CDI
Transmission Mode	Manual
Vehicle Commander	106in (2700mm)
Vehicle Width	57in (1450mm)
Car Height	76in (1940mm)
Wheelbase	70in (1790mm)
Track width	Front: 45.3in (1150mm) Rear: 45.3in (1150mm)
Minimum Ground Clearance	11.8in (300mm)
Seat Cushion Height	33.6in (854mm)
Turning Circle Radius	197in (5000mm)

More Specification	
Damping Form	Coil Spring Damping
Brake Type Main Brake	Hydraulic Disc Type One Drive Four
Emergency/ Parking Brake	Brake Rear Axle /Manual Operation
Rim Type	Aluminium
Tyre Specification	Front: 25* 8-12/ Rear: 25 * 10-12
Fuel Tank Volume	23L
Rated Load Capacity	794 lbs
Container Load	441 lbs
Max. Total Mass	1790 lbs
Frame	Steel Pipe Structure
Clutch Type	Automatic Clutch
Crankcase Lubricating Oil	SF-15W/40
Oil Capacity	41oz (1200ml)
Fuel Tank Capacity	6Gallons (23L)
Headlamps	35W LED White Light
Drive Mode	Rear Drive
Parking mode	Two Rounds
Parking Brake	Mechanical
Magneto Type	Flywheel Rotor Type DC Output
Number of Containers (40GP)	16
Package Size	91.7in x 57.5in x 49.6in



Maskinmægler.dk

- vi tager godt udstyr seriøst

